



OSCULATI **Antifouling**

For professional and DIY use





65.601.11



65.601.21

SP Classic 153 antifouling paint

Self-polishing antifouling paint based on copper salt free organic biocide.
Compatible with any hull (fibreglass, aluminium, wood, etc.).
Yield: 9 m²/l. Recommended for moderately aggressive weather conditions.
Minimum temperature of application 10° C.
Covering temperature: 6h at 20° C.
Curing time before launching: 12h at 20° C.

White	Blue	Black	Package	PACKAGE
65.601.11	65.601.12	65.601.13	0.75 l	6
65.601.21	65.601.22	65.601.23	2.5 l	4



65.611.14



65.611.24

HM Classic 153 antifouling paint

Hard matrix antifouling paint based on copper salt free organic biocide.
Compatible with any hull (fibreglass, aluminium, wood, etc.).
Yield: 9 m²/l, colour 7 m²/l.
Recommended for aggressive areas in the average.
Minimum temperature of application 10° C.
Covering temperature: 6h at 20° C. Curing time before launching: 12h at 20° C.

White	Blue	Black	Red	Package	PACKAGE
65.611.11	65.611.12	65.611.13	65.611.14	0.75 l	6
65.611.21	65.611.22	65.611.23	65.611.24	2.5 l	4



65.602.12



65.602.22

SP Premium 365 antifouling paint

Self-polishing antifouling paint based on copper oxide free organic biocide.
Compatible with any hull (fibreglass, aluminium, wood, etc.).
Yield: 8 m²/l, colour 7 m²/l.
Recommended for aggressive weather conditions all year round.
Minimum temperature of application 10° C.
Covering temperature: 6h at 20° C. Curing time before launching: 12h at 20° C.

White	Blue	Black	Package	PACKAGE
65.602.11	65.602.12	65.602.13	0.75 l	6
65.602.21	65.602.22	65.602.23	2.5 l	4



65.612.13



65.612.23

HM Premium 365 antifouling paint

Hard matrix antifouling paint based on copper oxide free organic biocide.
Compatible with any hull (fibreglass, aluminium, wood, etc.).
Yield: 8 m²/l.
Recommended for aggressive weather conditions all year round.
Minimum temperature of application 10° C.
Covering temperature: 6h at 20° C. Curing time before launching: 12h at 20° C.

White	Blue	Black	Package	PACKAGE
65.612.11	65.612.12	65.612.13	0.75 l	6
65.612.21	65.612.22	65.612.23	2.5 l	4



65.620.10



65.620.20

Sealer primer and sealant

Mono-component chlorine-caoutchouc primer.
Compatible with any antifouling paint on new vessels or suitable as sealant on aged antifouling paints.
Yield: 6.3 m²/l.
Covering time: 8h at 20° C.
Colour: metalized grey.

Metalized grey	Package	PACKAGE
65.620.10	0.75 l	6
65.620.20	2.5 l	4



65.621.10



65.621.20

Two-component epoxy primer

Two-component epoxy primer for no matter what vessel.
For use on any kind of surface, both bottom and upper works, resulting in an anti-corrosion and insulating film. Spread a thin layer to let antifouling paints cling to the surface (curing time 4 to 12 hours @ 20°C). Spread 2 to 4 thick bottom layers for two-component cycles (curing time 12 to 74 hours @ 20°C).

Code	Package	PACKAGE
65.621.10	0.75 l	6
65.621.20	2.5 l	2



65.625.10



65.625.20

MC Thinner

Thinner for one-component and antifouling paints.
For spray, brush and roller application.

Code	Package	PACKAGE
65.625.10	0.5 l	12
65.625.20	2.5 l	6

Paint brush with Ecolegno handle for varnish and paint

Blonde bristle paint brush with Ecolegno handle made from wood waste. It has a longer life than natural wood and resist humidity and solvents. For its metal ring and epoxy glue, it is a product suitable for water- or solvent-based varnish or paint. 100% Made in Italy.

Code	mm	Bristle length mm	PACKAGE
65.650.30	30 x 15	57	12
65.650.40	40 x 15	57	12
65.650.50	50 x 15	64	12
65.650.60	60 x 15	64	12



Paint brush with plastic handle for fiberglass

Blonde bristle paint brush with plastic handle and metal ring. Resistant to solvents. Ideal for fiberglass applications. 100% Made in Italy.

Code	mm	Bristle length mm	PACKAGE
65.651.30	30 x 15	44	12
65.651.40	40 x 15	50	12
65.651.50	50 x 15	50	12
65.651.60	60 x 15	50	12



Paint brush with long handle

Blonde bristle paint brush with 30-cm long plastic handle and metal ring. The epoxy glue makes it resistant to solvents. 100% Made in Italy.


Code	mm	Bristle length mm	PACKAGE
65.652.30	30 x 15	51	12
65.652.40	40 x 10	57	12
65.652.50	50 x 10	57	12



Paint rollers

High-quality professional paint rollers, 100% Made in Italy.


Code	Description	Ideal for	mm	Material	OPTIONAL handle	ORDER BY BOX	PACKAGE
65.653.00	Long-bristle roller	Antifouling - Fiberglass	50	10-mm polyamide	65.653.04	20	200
65.653.01	Long-bristle roller	Antifouling - Fiberglass	100	10-mm polyamide	65.653.05	10	100
65.653.02	Short-bristle roller	Gelcoat, thin paint (polyester), varnish, thin applications	50	4-mm velour wool	65.653.04	20	200
65.653.03	Short-bristle roller	Gelcoat, thin paint (polyester), varnish, thin applications	100	4-mm velour wool	65.653.05	10	100
65.653.06	Long-bristle creased roller	Antifouling - Fiberglass	200	13-mm polyamide	65.653.07	-	60



Handles for rollers

High-quality material for professional rollers. 100% Made in Italy.

Code	Description	mm	Suitable for
65.653.04	Handle for small roller	50	65.653.00; 65.653.02
65.653.05	Handle for small roller	100	65.653.01; 65.653.03
65.653.07	Handle for roller	200	65.653.06



Bubble blaster

65.653.08 Aluminium bubble blaster. Ideal to remove air bubble during fiberglass lamination.



Tray

65.653.09 Plastic tray for paints, 180x220-mm size.



How to choose

Osculati antifouling paints do not contain copper and therefore are fit **for any kind of hull** (fiberglass, aluminium, wood, etc.).

Both **self-polishing** and **hard-matrix** antifouling paints are available on the market:

- Self-polishing antifouling paints are gradually subject to wear over time and therefore help maintain the hull clean. They are meant to last all season if applied on sailboats and not too fast boats (up to 25 knots).
- Hard-matrix antifouling paints will not wear out through use and therefore their function is essentially chemical. Suitable for fast boats (over 25 knots) and long cruises.

HARD-MATRIX

- good abrasion resistance
- for boats whose speed is > 25 knots

SELF-POLISHING

- smooth surface and good film solubility
- for sailing or motor boats whose speed is < 25 knots

Boat type		Hard matrix		Self-polishing matrix	
		HM-Classic 153 65.611.xx	HM-Premium 365 65.612.xx	SP-Classic 153 65.601.xx	SP-Premium 365 65.602.xx
Always in water			X		X
Seasonal use		X		X	
Up to 25 knots	Fiberglass			X	X
	Wood			X	X
	Steel			X	X
	Aluminium			X	X
Over 25 knots	Fiberglass	X	X		
	Wood	X	X		
	Steel	X	X		
	Aluminium	X	X		
Fresh water		X	X	X	X
Salt water		X	X	X	X

N.B. Prior to the antifouling paint always apply 2 coats of Primer Sealer 65.620.10/20 or 1 coats of two-component epoxy Primer 65.621.10/20

Application: approximate liters of 2 coats of antifouling paint

Meters lenght		6	7	8	9	10	11	12	13	14	15
Liters	Sail boat	3	3	4,5	5,25	6	6,75	8,25	9	10,5	12
	Motor boat	3	4,5	6	7,5	9	10,5	12,75	14,25	16,5	18

OSCOLATI Antifouling

For professional and DIY use

Antifouling and painting materials





Osculati S.r.l.

Via Pacinotti, 12 - 20090 Segrate (MI)

Tel +39 02 2699 111 - info@osculati.it

Osculati & C. S.p.A.

Via di Sottopoggio - 55012 Capannori (LU)

Tel +39 0583 403 232 - info@lucca.osculati.it

Code 70.199.30-04EN

